

P15 1.5T ELECTRIC PALLET TRUCK







P15 1.5T ELECTRIC PALLET TRUCK

TECHNICAL SPECIFICATIONS

		U J

CHARACTERISTICS	Model		P-15
	Power unit		Battery
	Operation		Walkie Type
	Rated traction weight	Q (t)	1.5
	Load centre	c (mm)	600
	Axle centre to fork face	x (mm)	875
	Wheel base	y (mm)	1202
WEIGHTS	Service weight with battery	kg	193/200
WHEELS/TYRES	Wheels type		PU Tire
	Driving wheel size	Φ×w(mm)	Ф210×70
	Bearing wheel size	Φ×w(mm)	Ф80×60
	Wheels, number front/rear (x = driven)		4/1x
	Track width	b11 (mm)	410/535
DIMENSIONS	Lift	h3 (mm)	200
	Overall height(With handle	h14 (mm)	612/1195
	Lowered length	h13 (mm)	85
	Overall length	l1 (mm)	1628
	Length to fork face	l2 (mm)	478
	Overall width	b1/ b2 (mm)	560/685
	Fork dimensions	s/e/l (mm)	50/150/1150
	Width of forks	b5 (mm)	560/685
	Min.Ground clearance	m2 (mm)	35
	Aisle width with pallet 1000 x 1200 across forks	Ast (mm)	1828
	Aisle width with pallet 800 x 1200 along forks	Ast (mm)	1878
	Min.Turning radius	Wa (mm)	1352
PERFORMANCE	Travel speed,laden/unladen	(km/h)	4.2/4.5
	The max Lifting speed, laden/unladen	(mm/s)	22/25
	Lowering speed, laden/unladen	(mm/s)	38/28
	Max.gradient performance, laden/unladen	(%)	6/10
	Service brake		Electromagnetic braking
DRIVE	Drive motor, 60 minute rating	(kW)	0.75
	Lift motor rating at S3 15%	(kW)	0.8
	Battery according to DIN 43531/35/36 A,B,C,no	(KVV)	
	Battery voltage/rated capacity	(V/Ah)	2×12/75
	Battery weight (± 5%)	(kg)	40
	Sattery Weight (= 570)	(kg)	
OTHERS	Type of drive control		DC Motor
	Noise level at operator's ear	(dB(A))	67
	Steering type		Mechanical steering

DISCLAIMER: Specifications, features, and availability may vary by model and are subject to change without notice. Images are for illustrative purposes only. Actual product may differ. Performance may vary depending on application, conditions, and operator skill. Always operate machinery in accordance with safety guidelines and local regulations.

1300 039 225